



LEAKS OF THE MIXER BUT OVER THE TOP

Replacement of the two gacos (kind of 'O' Ring)

SWITCH-OFF THE WATER PUMP

SWITCH ON THE WATER PUMP



1 DISCONNECT THE COLD AND WARM INLET HOSES FROM THE S/S HOSES OF THE MIXER (MARK THE ONE OF HOT WATER)



2 UNSCREW THE BRASS NUT (11 MM KEY) UNDER THE TOP FROM THE STUD AND SLIP OFF THE METAL HALFMOON PLATE AND THE RUBBER GASKET



3 PULL-UP THE MIXER FROM THE TOP



4 UNSCREW BY HAND THE LOWER BASEPLATE



5 PULL OUT THE LOWER BODY WITH THE SPOUT



6 REPLACE THE TWO GACOS (KIND OF 'O' RING) KEEPING THE WIDERSIDE FACING EACH OTHER



#17115

CONNECT THE INLET HOSES TO THE FLEXIBLE HOSES CONNECTED TO THE MIXER TAKING CARE OF THE POSITION OF THE HOT WATER

UNDER THE TOP: PULL-IN THE HALFMOON PLATE WITH ITS RUBBER GASKET SCREW THE BRASS NUT ON THE THREADED STUD

PLACE THE MIXER IN THE ITS PLACE

SCREW IN THE LOWER BASEPLATE CHECKING THAT THE TEFLON GASKET IS IN PLACE AS WELL AS THE LOWER 'O' RING

PULL IN CAREFULLY THE LOWER BODY TAKING CARE NOT TO DAMAGE THE GACO AND THE TEFLON GASKET

CHECK THE TWO WHITE TEFLON GASKET AND, IF DAMAGED, REPLACE THEM

